

17AE43

Fourth Semester B.E. Degree Examination, Aug./Sept.2020 **Aircraft Propulsion** 

Max. Marks: 100

Note: Answer any FIVE full questions, choosing ONE full question from each module.

# Module-1

- With the help of PV and TS diagram, explain the cycle analysis of Jet engine. (12 Marks)
  - Derive an expression for steady flow energy equation for compressible flow machines with usual notation. (08 Marks)

#### OR

- With the help of a neat schematic and PV and TS diagram, explain the working principle of 2 a four stroke diesel engine. (10 Marks)
  - b. What are the advantages of gas turbine engines over reciprocating engine? (06 Marks)
  - c. Define the following:
    - (i) Stagnation velocity of sound (ii) Stagnation pressure (04 Marks)

# Module-2

- Explain the working principle of a turbojet engine with the help of a neat schematic, PV and 3 T-S diagram. What are its advantages and disadvantages? (12 Marks)
  - b. A turbojet power plant uses aviation kerosene having a calorific value of 43 MJ/kg. The fuel consumption is 0.18 kg-N/hr, when the thrust is 9 kN. The aircraft velocity is 500 m/s the mass of air passing through the compressor is 27 kg/s. Calculate the air-fuel ratio and overall efficiency. (08 Marks)

- With the help of a neat sketch explain the working principle of an after burner. (06 Marks)
  - Define a propeller and explain the different types of propellers.
  - (06 Marks) c. The diameter of the propeller of an aircraft is 2.5m. It flies at a speed of 500 kmph at an altitude of 8000m. For a flight to get speed ratio of 0.75, determine
    - (i) the flow rate of air through the propeller
    - (ii) the thrust produced.
    - (iii) specific thrust
    - (iv) specific impulse
    - (v) the thrust power.

Take at Z = 8000m, air density  $\rho = 0.525 \text{ kg/m}^3$ 

(08 Marks)

### Module-3

- With the help of a neat sketch explain the method of shock swallowing using variable area 5
  - b. Explain with a neat sketch the operation of subsonic inlet under various flow speed conditions. (06 Marks)
  - c. Air ( $\gamma$  = 1.4, R = 287.43 J/kg °K) enters a straight axisymmetric duct at 300 K, 3.45 bar and 150 m/s and leaves it at 277 K, 2.058 bar and 260 m/s. The area of cross section at entry is 500 cm<sup>2</sup>. Assuming adiabatic flow, determine (i) Stagnation temperature (ii) Maximum velocity (iii) Mass flow rate (iv) area of cross section at exit. (06 Marks)

#### OR

- 6 a. With the help of a neat sketch explain
  - (i) Over expanded nozzle (ii) Under expanded nozzle. (12 Marks)
  - b. With the help of neat diagram, explain the different modes of inlet operations. (08 Marks)

## Module-4

- 7 a. Describe the essential parts of a centrifugal compressor, with the help of a neat sketch. Explain the principle of operation. (10 Marks)
  - b. A centrifugal compressor under test gave the following data:

    Speed = 11,500 rev/min, Inlet total head temperature = 21°C outlet and inlet total head pressure = 4 bar and 1 bar. Impeller diameter = 75 cm. If the slip factor is 0.92, what is the compressor efficiency?

    (10 Marks)

#### OR

8 a. Define and derive an expression for degree of reaction of an axial flow compressor.

(10 Marks)

- b. Explain the process of surging and stalling in an axial flow compressor. (06 Marks)
- c. Derive an expression for compressor efficiency in centrifugal compressor. (04 Marks)

## Module-5

- 9 a. Explain different types of combustion chambers used in gas turbine engine. Briefly discus their advantages and disadvantages. (10 Marks)
  - b. Explain the following:
    - (i) Flame tube cooling
    - (ii) Use of Cheaper fuels
    - (iii) Pollution

(10 Marks)

#### OR

10 a. With the help of a neat sketch, explain the working of a single stage reaction turbine.

(06 Marks)

- b. Explain the different methods of cooling turbine blades with relevant sketch. (06 Marks)
- c. A multistage gas turbine is to be designed with impulse stages and is to operate with an inlet pressure and temperature of 6 bar and 900 K and an outlet pressure of 1 bar. The isentropic efficiency of the turbine is 85%. All the stages are to have a nozzle outlet angle of 75° and equal outlet and inlet blade angles. Mean blade speed of 250 m/s and equal inlet and outlet gas velocities. Estimate the maximum number of stages. Take  $\gamma = 1.33$ ,  $C_p = 1.15$  kJ/kg °K and optimum blade speed ratio.

\* \* \* \* \*