18MT72

Seventh Semester B.E. Degree Examination, Feb./Mar. 2022 Thermal Engineering

Time: 3 hrs.

Max. Marks: 100

Note: 1. Answer any FIVE full questions, choosing ONE full question from each module. 2. Heat transfer handbook is permitted.

Module-1

- Define the following:
 - Open system i)
 - ii) Closed system
 - Intensive property iii)
 - Extensive property iv)
 - Thermodynamic state point V)

 - Thermodynamic process. vi)

(06 Marks)

Explain Quasistatic process with a neat sketch.

(06 Marks)

State the Zeroth law of thermodynamics. Explain thermodynamic equilibrium.

(08 Marks)

OR

Derive an expression for displacement work of polytropic process with P-V diagram. 2 a.

(08 Marks)

State and explain thermodynamic definition of work. b.

(06 Marks)

A fluid expands frinctionlessly in a closed system from a volume $0.1 \, \text{m}^3$ to $0.16 \, \text{m}^3$ in such a where C is constant. The initial pressure is manner that the pressure is given by P =(06 Marks) 300Pa. Calculate the amount of work done.

Module-2

- Derive an expression for Steady Flow Energy Equation (SFEE) with suitable assumptions. 3 a. (08 Marks)
 - With PV diagram define first law of thermodynamics under cycle process.

(04 Marks)

A steam turbine is shown in Fig.Q.3(c) with properties at inlet and outlet. The mass flow rate of steam is 40kg/s. Calculate power developed by the turbine. Neglect heat interaction.




Fig.Q.3(c)

(08 Marks)

2. Any revealing of identification, appeal to evaluator and /or equations written eg, 42+8 = 50, will be treated as malpractice. Important Note: 1. On completing your answers, compulsorily draw diagonal cross lines on the remaining blank pages.

OR

- 4 a. State the Kelvin Plank and Claussius statement and explain its equivalent of the two statements. (08 Marks)
 - b. Explain PMM-I and PM-II kind.

(04 Marks)

c. Derive an expression for COP of refrigerator and heat pump.

(08 Marks)

Module-3

- 5 a. Derive an expression for air standard efficiency of Otto cycle with P.V. diagram and T-S diagram. (10 Marks)
 - b. Define the following: i) Mean effective pressure

ii) Air standard efficiency.

(04 Marks)

c. Compare Otto, diesel and dual cycles.

(06 Marks)

OF

6 a. Explain the modes of heat transfer with governing law and equations.

(12 Marks)

b. Explain three kinds of boundary conditions.

(06 Marks)

c. Define the following: i) Thermal conductivity ii) Heat transfer coefficient.

(02 Marks)

Module-4

- 7 a. Derive the 3D conduction equation in Cartesian coordinator and reduce the equation to Fourier and Laplace equation. (12 Marks)
 - b. A furnace wall is made of 3 layers. First layer is of insulator brick of 12cm thickness (K = 0.6W/mK). The face is exposed to gases at 870°C with convection coefficient of 110W/m²K. It is covered with 10cm thick layer of fire brick. (K = 0.8W/mK) with a constant resistance of 2.6 × 10⁻⁴m²/kW between 1st and 2nd layer. The 3rd layer is a plate of 10cm thickness (K = 4W/m K) with a constant resistance between 2nd and 3rd layer of 1.5 × 10⁻⁴m²K/W. The place is exposed to air at 30°C with convection coefficient of 15W/m²K. Determine the heat flow and overall heat transfer coefficient. (08 Marks)

OP

- 8 a. Using dimensional analysis for the free convection heat transfer show that $N_u = f(Gr, Pr)$.
 - b. Explain the following:
 - i) Natural convection
- ii) Local heat transfer coefficient
- iii) Grasshoff number

- iv) Nusselt number
- v) Drag coefficient.

(10 Marks)

Module-5

- 9 a. Explain the physical significance of the following: i) Reynolds number ii) Staton number iii) Prandtl number iv) Nusselt number. (08 Marks)
 - b. Using Buckingham π -theorem for forced convection heat transfer show that $N_u = C(R_e^m, P_r^n)$ with usual notations. (12 Marks)

OR

- 10 a. State and explain following radiation laws: i) Plank's law
 iii) Stefan-Boltzmann law iv) Kirchoff's law.

 iii) Wein's displacement law
 (12 Marks)
 - b. Two large parallel plates having emissivities at 0.3 and 0.5 are maintained at temperature of 800°C and 300°C respectively. A radiation shield having an emissivity of 0.05 on both sides is placed between the 2 plates. Calculate: i) heat transfer per unit area without shield ii) Find the temperature of the shield and heat transfer per unit area with shield. (08 Marks)

* * * * *