

CBCS SCHEME

USN

--	--	--	--	--	--	--	--	--	--

15ENG46

Fourth Semester B.Arch. Degree Examination, Aug./Sept.2020 Specification, Quantity and Costing of Buildings

Time: 3 hrs.

Max. Marks: 100

Note: Answer any FIVE full questions, choosing ONE full question from each module.

Module-1

- 1 a. What is an estimate? (02 Marks)
b. Explain:
i) Item rate estimate
ii) Supplementary Estimate (12 Marks)
iii) Plinth Area Estimate. (06 Marks)
c. Explain Earnest Money Deposit and Security Retention. (06 Marks)

OR

- 2 Write detailed technical specification to the following items of work.
a. Earthwork excavation for foundation in hard soil. (06 Marks)
b. Providing and laying PCC M20 grade concrete for Roof slab. (07 Marks)
c. Providing and constructing Burnt brick masonry is CM1:6 for super structure using table moulded bricks. (07 Marks)

Module-2

- 3 Fig.Q.1 shows the plan of 3 roomed Residential Building with sections enclosed. Calculate the Quantity of below mentioned items of work only by centre line method.
a. Calculate of Net length for below mentioned items. (08 Marks)
b. Earthwork excavation for foundation in hand soil. (04 Marks)
c. Providing and laying PCC 1:4:8 for foundation. (04 Marks)
d. Providing and laying PCC 1:3:4 for foundation Plinth as D.P.C. (04 Marks)

OR

- 4 Fig.Q.2 shows the plan and section of column footing, calculate the below mentioned quantities for 10 such columns.
a. Earthwork excavation for foundation in hard soil. (03 Marks)
b. Providing and laying PCC 1:4:8 for foundation. (02 Marks)
c. Providing and laying M20 grade concrete for footing. (07 Marks)
d. Providing and laying M20 grade concrete for pedestal. (03 Marks)
e. Providing and laying M20 grade concrete for columns. (05 Marks)

Module-3

- 5 a. What is basic cost? Why is basic cost fixed in a project? Briefly explain. (08 Marks)
b. In the tender, basic cost of steel for reinforcement is Rs.55000/MT. The total quantity of steel used is 15.00MT for entire project, and average purchase price is Rs.60,000/MT. Write if the contractor is eligible to claim the difference in cost or pay the owner. (06 Marks)
c. What are factors affecting the rate when the analysis is made? (06 Marks)

OR

- 6 From the 1st principles, Conduct Rate Analysis for below mentioned items of work.
- Providing and laying PCC 1:4:8 for foundation using 40mm and down size coarse aggregates. (06 Marks)
 - Providing and constructing burnt brick masonry is CM1:6 for superstructure using table moulded bricks. (07 Marks)
 - Random rubble masonry in CM1:6 for foundation using hammer dressed stones. [Basic cost of cement → Rs.350/Bags, Sand → Rs.3500/mt³, coarse aggregate 40mm → Rs.635/mt³, Bricks → Rs.900/No stones Rs.18.00/No]. (07 Marks)

Module-4

- 7 The details of 3 Bed Room unit is shown in Fig.1. Calculate the below mentioned items of work by centre line method.
- Providing and constructing size stone masonry is CM1:6 for foundation. (08 Marks)
 - Providing and constructing Burnt brick masonry is CM1:6 for super structure only main walls. (10 Marks)
 - Providing and fixing door frame and paneled shutter. (02 Marks)

OR

- 8 Following items of works are to estimated for an interior fit out. Prepare a detailed estimate.
- Provide and laying false ceiling with necessary frame work and plaster of Paris. (06 Marks)
 - Providing and laying 2 coats of plastic Emulsion Paint to ceiling and Internal walls over a coat of primer. (08 Marks)
 - Providing and laying Marble flooring in CM1:6. With necessary pointing.
Size of office room → 12.0mt × 8.0mts
Door D → 1.00mt × 2.10mts – 1No
Window W → 1.50mt × 1.50mts → 3No's
Height of office room → 3.50mts
Skirting Height → 0.10mt (06 Marks)

Module-5


- 9 The Fig.Q.3 enclosed shows the details of septic tank. Estimate the below mentioned items of work only.
- Earth work excavation for foundation in hard soil. (04 Marks)
 - Providing and laying PCC 1:4:8 for foundation using 40mm and down size coarse aggregates. (03 Marks)
 - Providing and constructing Burnt brick masonry is CM1:4 for the side walls of septic tank. (09 Marks)
 - Providing and laying M20 grade concrete for Roof slab using 20mm and down size coarse aggregates. (04 Marks)

OR

- 10 Estimate the Quantity of Earth work required for 180mts lengths of road by "Mean depth method" from following data. Formation width = 10mts, side slope 2H:1V.

Chainage in mts	0	30	60	90	120	150	180
RL of ground in mts	112.0	111.80	111.70	111.60	111.50	111.30	111.40
Formation level in mts	←————— 112.60mts —————→						

(20 Marks)





A	B	C	D	E	F	G	H
2.0mt	2.0mt	1.8mt	0.45mt	0.6mt	0.50	0.30mt	0.45mt

Column size → (0.23 × 0.45)

Height of column above pedestal → 5.0mts

Fig.Q.2

SECTION OF SEPTIC TANK X-X



Plan of septic tank

Fig.Q.3
