	A P.	
	E LIPRARY	
USN	Date M. [6]	
L	88un yer	

09ENG 5.5

Fifth Semester B. Arch Degree Examination, June/July 2015 Structures - V

school o

Time: 3 hrs. Note: Answer any FIVE full questions,

Max. Marks: 100

a. Define workability of concrete and explain factors affecting it.

(06 Marks) (06 Marks)

b. Explain the importance of water cement ratio.

- c. Specify groups of concrete based on grades of concrete as per code. Also specify minimum grade of concrete for every severe exposure and extreme exposure mention relevant code clauses.
- Determine the moment of resistance of a singly reinforced beam 160mm wide and 300mm deep to the centre of reinforcement, if the stresses in steel and concrete are not to exceed $140\,\mathrm{N/m^2}$ and $5\,\mathrm{N/m^2}$. The reinforcement consists of 4 bars of 16mm diameter take m = 18. If the above beam is used for an effective span of 5m, find the maximum load the beam can carry.
- 3 Design the necessary reinforcement for a reinforced concrete beam 300 × 450mm to carry a u.d.l of 25 kN/m over a span of 4m. The beam is supported on a 400mm thick wall at ends use M₂₀ concrete and Fe₄₁₅ steel. Take effective cover as 40mm. (20 Marks)
- A T-beam of span 8m carries a live load of 10kN/m² and a floor finish of 0.6kN/m². Spacing of T-beam is 3.2m. Thickness of slab is 125mm width of web is 300mm. Total depth of beam is 450mm, load factor is 1.5 use M₂₀ concrete and Fe₄₁₅ steel. Design the beam take effective cover as 50mm. (20 Marks)
- a. Design an R.C.C slab of $4m \times 12mm$ supported on a brick massonary wall 300mm thick. Live load on the slab is $3kN/m^2$ and floor finish = $1kN/m^2$. Use M_{20} and Fe_{415} , take thickness of slab as 125 mm and effective cover as 20mm. (10 Marks)
 - Design a R.C slab of $5m \times 9m$ supported on brick massonary 300mm thick. Live load on the slab is $3 \, kN/m^2$ and floor finishing is $1 \, kN/m^2$. Use M_{20} and Fe_{415} , take thickness of slab as 125 mm and effective cover as 105mm. (10 Marks)
- a. Design the necessary reinforcement for a circular column of diameter 450m. the column is to carry a factored load of 1500 kN. Use M₂₀ and grade-1 mild steel.
 - Design the necessary reinforcement for an R.C column 300×450 mm of length 3.4m to carry an axial load of 1200kN M_{20} and Fe_{415} are used. (10 Marks)
- Design a dog-legged staircase for a public building using $\,\mathrm{M}_{20}\,$ concrete and $\,\mathrm{Fe}_{415}\,$ steel. The distance between two floor is 3.2m size of the staircase room is $3m \times 4.5m$.
- A rectangular column of size 350mm × 550mm carries a live load of 1800kN. The safe 8 bearing capacity of soil is $150 \mathrm{kN/m^2}$ use $\mathrm{M_{25}}$ and $\mathrm{Fe_{415}}$ steel. Design a rectangular footing to support the column and sketch the details of reinforcement. (20 Marks)