

09ARC66

## Sixth Semester B.Arch. Degree Examination, Feb./Mar. 2022 Estimating and Costing

Time: 3 hrs. Max. Marks: 100

Note: 1. Answer Q.No.1 compulsory and any FOUR from Q.No.2 to Q.No.8.


2. Follow written dimensions only.

3. Missing data, if any, may be suitably assumed.

1 Estimate the below mentioned items of work [ Refer Fig.Q1 ].

(40 Marks)

- Calculate centre line-calculations
- b. Earthwork excavation for foundation @ Rs. 200 per cu.m
- c. P.C.C Bed foundation (1:4:8)@ Rs. 300 per cu.m.
- d. First class brick masonry foundation @ Rs. 1500 per cu.m.



- Write a technical specification for any three of the following:
  - a. First class brick work in super structure in CM (1:6)
  - b. Cement plastering in CM (1:4)
  - c. R.C.C. (1:2:4) for roof slab
  - d. Random rubble stone masonry in CM (1:6).

(15 Marks)

- Work out from the first principles, the rate analysis for any three of the following:
  - a. PCC (1:4:8) for foundation bed
  - b. 12 mm thick plastering in CM (1:6) in superstructure
  - c. 25 mm thick cement concrete flooring of (1:2:4)
  - d. Coursed rubble stone masonry in CM (1:6) for foundation.

(15 Marks)

Reduce level (RL) of ground along the centerline of proposed road from chainage 10<sup>th</sup> to 20<sup>th</sup> chainage are given below. The formation level at the 10<sup>th</sup> chainage is 107 M and the road is downward gradient of 1 in 150 upto the chainage 14<sup>th</sup> and then the gradient charges to 1 in 100 downward. Formation width of road is 10 meters and side slopes of banking are 2:1 (horizontal: vertical). Length of the chain is 30 M. Draw longitudinal section of the road and a typical cross-section and prepare estimate of the earth work at the rate of Rs.275/m<sup>3</sup>.

1	Chainage	10	11	12	13	14	15	16	17	18	19	20
	R.L. of ground (M)	105.00	105.60	105.44	105.90	105.42	104.30	105.00	104.10	104.62	104.00	103.30

## 09ARC66

- The steel quality is to be computed diameter wise from following data: 5
  - b. Size of column footing  $1.5 \times 1.5$ m in plan

Steel provided for footing – 10mm ▼ 15cm c/c both ways

Cross section of column  $-30 \text{cm} \times 30 \text{m}$ 

Main reinforcement of column - 4 - 20mm ₹ 4 - 16mm ₹

Ties 8mm ₹ @ 10 cm c/c

Height of column - 5mt

Weight of 8mm – 4kg/mt

10mm - 6 kg/mt

16mm - 1.6 kg/mt


20mm - 2.5 kg/mt.

(15 Marks)

- Calculate the quantity of earth work for 400mt length for a portion of road in a uniform 6 ground the height of bank at two ends begin 7 and 1.4. The formation width is 7.0mt and side slope 2:1 (horizontal to vertical). Assume that there is no transverse slope. Calculate (15 Marks) the quantity using method -I.
- 7 Write short notes on any Three of the following:
  - a. Lump sum contract
  - b. Overhead costs
  - c. Schedule of rates
  - d. Bill of quantities

(15 Marks)

Prepare a detailed estimate of a R.C.C. beam of 8m clear span and 75cm × 40cm in section 8 from the given drawings. Steel in detail and R.C.C. work shall be calculated separately. [Refer Fig.Q8]



(15 Marks)