



--	--	--	--	--	--	--	--	--	--

## Fourth Semester B.E. Degree Examination, June/July 2024 Turbomachines

Time: 3 hrs.

Max. Marks: 100

Note: Answer any FIVE full questions, choosing ONE full question from each module.

### Module-1

- 1 a. Distinguish between a turbomachine and a positive displacement machine. (06 Marks)  
b. What is a turbomachine? With a neat sketch, explain the principle components of turbomachine. (06 Marks)  
c. From the performance curve of a turbine, it is seen that a turbine of 1m diameter acting under a head of 1m develops a speed of 25rpm. Determine the diameter of the prototype, if it develops 10,000kW, working under a head of 200m with a specific speed of 150rpm. (08 Marks)

OR

- 2 a. Derive the basic Euler Energy equation for a turbomachine. (10 Marks)  
b. A model of Francis turbine of 1:5 scale ratio is tested under a head of 1.5. If developed 3kW at 360rpm. Determine the speed and power developed under a head of 6m. (05 Marks)  
c. An output of 10kW was recorded on a turbine, 0.5m diameter, revolving at a speed of 800rpm, under a head of 20m. Determine the diameter and output of another turbine which works under a head of 180m at a speed of 200rpm, when their efficiencies are same. (05 Marks)

### Module-2

- 3 a. What is polytropic efficiency in the compression process? Formulate the corresponding equation. (08 Marks)  
b. An air compressor has the following data. Inlet pressure = 1.02br, Exit pressure = 1.5bar, Inlet temperature = 300K, Exit temperature = 340K. Determine : i) the isotropic compression efficiency ii) Polytrophic efficiency. (06 Marks)  
c. An air compressor has 6 stages of equal pressure ratio of 1.4. The overall isentropic compression efficiency is 84%. Entry pressure is 1 br and  $T_1 = 40^\circ\text{C}$ . Determine the state of air at the exit.  $[\gamma = 1.4, R = -0.287\text{kJ/Kg.K}, C_p = 1.005\text{kJ/Kg.K}]$ . (06 Marks)

OR

- 4 a. With reference to a compression process, explain stage efficiency, Represent the same on separate T-S or h-s diagram. (06 Marks)  
b. A jet of gas has the following data : Temperature = 593K,  $\gamma = 1.3$ ,  $R = 469\text{J/Kg.K}$ , Mach No = 1.2. Determine for static and stagnation condition, i) Velocity of sound, Enthalpy. (06 Marks)  
c. Define reheat factor and explain the same. (08 Marks)

### Module-3

- 5 a. Explain the phenomena of surging and choking in a compressor. (08 Marks)  
b. What is a diffuser? Explain with a neat sketch. (06 Marks)  
c. Free air delivered by compressor is 20Kg/min. The inlet conditions are 1bar and  $20^\circ\text{C}$ , static. The velocity of air at the inlet is 60m/s. The isentropic efficiency of the compressor is 0.7. The total head pressure ratio is 3. Determine the total head temperature at the exit. (06 Marks)

Important Note : 1. On completing your answers, compulsorily draw diagonal cross lines on the remaining blank pages.  
2. Any revealing of identification, appeal to evaluator and /or equations written eg. 42+8 = 50, will be treated as malpractice.

OR

- 6 a. A two stage centrifugal compressor delivers  $500\text{m}^3$  of free air per min. The suction conditions are 1bar and  $15^\circ\text{C}$ . The compression ratio and isentropic efficiency of each stage are 1.25 and 80% respectively. Determine the isentropic efficiency for the entire compression process. (10 Marks)
- b. Air at a temperature of 290K, flows in a centrifugal compression running at 20,000 rpm, slip factor = 0.8,  $\eta_{t,i} = 0.8$ ,  $d^2 = 0.6\text{m}$ . Assume that the absolute velocity at the inlet and outlet are same. Determine the temperature rise of air passing through the compressor. (10 Marks)

Module-4

- 7 a. Mention different types of losses in a radial flow turbine and define nozzle loss coefficient. (10 Marks)
- b. The output of a 3 stage gas turbine is 30mW at the shaft coupling at an entry temperature of 1500K. The overall pressure ratio across the turbine is 11 and efficiency 88%. If the pressure ratio of each stage is same, determine : i) pressure ratio of each stage ii) Polytropic efficiency. Assume  $\gamma = 1.4$ ,  $C_p = 1.005\text{kJ/Kg.k}$ . Assume an efficiency of 91% to take into account shaft losses due to disc and bearing friction. (10 Marks)

OR

- 8 a. With reference to flow passage, write a brief description of subsonic, transonic and supersonic turbine. (10 Marks)
- b. Show that the overall isentropic turbine efficiency is greater than the stage efficiency for an expansion process. (10 Marks)

Module-5

- 9 a. Explain the working of Kaplan Turbine with neat sketch. (10 Marks)
- b. An axial flow pump is required to discharge  $1.25\text{m}^3/\text{s}$  of water, while running at 500rpm. The total head is 3.9m. If the speed ratio, is 2.3, flow ratio = 0.51, hydraulic efficiency = 0.87 and the overall pump efficiency is 0.82, determine : i) Power delivered to the water and the power input ii) The impeller hub diameter and tip diameter. (10 Marks)

OR

- 10 a. Draw the inlet and exit velocity triangles for a Pelton wheel turbine. Formulate an expression for the maximum hydraulic efficiency. (10 Marks)
- b. Draw Pelton wheel has a water supply rate of  $5\text{m}^3/\text{s}$  at a head of 256m and runs at 500rpm. Assuming turbine efficiency of 0.85, a coefficient of velocity for nozzle as 0.985, nozzle speed ratio of 0.46, determine : i) Power output ii) Specific speed iii) Number of jets iv) Diameter of the wheel v) Jet diameter. (10 Marks)

\*\*\*\*\*